



## MRK SERIES RACK, 44 RU, 26"D

MRK-4426-AV-AB |

### FEATURES & BENEFITS

Specify MRK series when you need an enclosure built to perform like a workhorse. Its rugged, space-saving design and high seismic load rating make it a favorite of installing contractors, particularly on larger-scale multi-bay jobs. The MRK series also offers seismic certification and open or removable sides.



- Fully welded construction for strength
- Racks gang together when fully loaded
- Standard front and rear adjustable 10-32 threaded rackrail with numbered spaces
- Includes standard configurable rear door and solid front door
- Comes configured with integrated fan top, vent blockers, and rear door vent
- Includes LACE-OP lacer strip, 4 straight and 2 offset lacer bars, 12 Velcro straps
- Includes 20A, 20 outlet corded power strip (PDT-2020C-NS)
- Includes 10-32 threaded rack screws, 100 qty, and 4 leveling feet
- Includes ganging hardware

### SPECIFICATIONS

#### GENERAL INFO

Finish: Black Powder Coat  
UL Standards Tested: UL1678

#### LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

ASCE: 7-10  
RoHS: Yes  
Greenguard: Yes  
UL Listing No: E173107

#### DIMENSIONS

Usable Depth: 24  
Usable Height: 77.125  
CFM: 550  
Panel Width: 19  
Capacity Weight (US): 10000  
Depth (US): 26.4  
Height (US): 83.125  
Width (US): 22  
Rack Units: 44

#### TECHNICAL INFORMATION

Rackrail Type: 10-32  
Seismic Load Capacity: 1050  
Static Load Capacity: 10000  
UL Load Capacity: 2500  
Material: Steel  
Mounting: Horizontal  
Seismic Rating: Yes